	.45 HWR)		HANGER BRACKET (4 PLACES)	.75 (4P CWS) (2P CWS) 14.28 7.14 (4P CWS) (2P CWS/HWS) 5.65 (DRN)
4.5 CENTERLINE LEFT SIDE VIEW STANDARD HEIGHT	PRIMARY AIR CONNECTIO FOR FIELD SEALING OF UN 6" DIA. PRIMARY AIR CONNECTION (R) 7/8" O.D. (4 PIPE - HWR) 7/8" O.D. (4 PIPE - HWS)		6" DIA. PRIMARY AIR CONNECTION PRESSURE TAP 7/8" O.D. (4 PIPE - CWR) (2 PIPE - CWR/HWR) 7/8" O.D. (4 PIPE - CWS) (2 PIPE - CWS) (2 PIPE - CWS/HWS) 3/4" FNPT DRAIN CONNECTION	.75 (4P ((2P (11.28 4.26 (4P CWS) (2P CWS/HWS)
PERFO		75 16.50 .75 40.50 16.78		2.70 (DRN) * FOR FOR FOR PROPRIETARY AND CONFIDENTIA THE INFORMATION CONTAINED IN THIS VOR THE SOLE PROPERTY OF RITTLING, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTE PERMISSION OF RITTLING IS PROHIBITED.



